

Armaflex®
Alu

THE FLEXIBLE INSULATION WITH
SILVER FINISH FOR BETTER AESTHETICS



- Better aesthetics
- Easy to clean
- Durable and high resistance to mechanical abuse

- Aesthetically appealing silver finish
- Very high water vapour diffusion resistance - $\mu \geq 12,000$
- Excellent fire resistance



Technical Data - Armaflex Alu

Brief Description	Highly-flexible, closed-cell insulation material with high water vapour diffusion resistance and low thermal conductivity					
Material Type	Elastomeric foam based on synthetic rubber (NBR), with reinforced Aluminium Foil facing					
Colour	Silver					
Material Special Information	Laminated with 12 micron Aluminium foil, with reinforced glass scrim					
Product Range	Available in sheets, in 6 mm, 9 mm, 13 mm, 16 mm, 19 mm, 25 mm & 32 mm Thickness. 1000 mm wide rolls Armaflex Alu (CO) Precovered Tubes are available in 9 mm, 13 mm, 19 mm, 25 mm & 32 mm thickness. 1000 mm long tubes					
Applications	For Insulating air-conditioning air ducts to prevent condensation and save energy. Preferred by pharma company					
Special Features	Provides aesthetic bright silver finish and smooth surface; attracts less dust and easy to clean surface with high resistance to mechanical abuse					
Safety and Environment	ODP zero GWP zero Dust & fibre free					
Assembly	Light weight. Closed cell structure means no additional vapour barrier required					
Property	Value/Assessment					Special Remark
Temperature Range						
Temperature Range	max. service temperature	+ 105 °C			(+85 °C if sheets or tape is glued to the object with its whole surface)	Tested acc. to EN 14706 EN 14707 & EN 14304
	min. service temperature	0 °C				
Thermal Conductivity						
Thermal Conductivity	ϑ_m	0 +20 +40			[°C]	Tested acc. to EN 12667 EN ISO 8497
	λ	≤	0.035	0.037	0.039	
Water vapour diffusion resistance						
Water vapour diffusion resistance	μ	≥	12,000			Tested acc. to EN 12086 EN 13469
Fire Performance						
Reaction to Fire	Fire performance acc. to building regulation	Class O				Surface Spread of Flame: tested acc to BS 476 Part 7:1997 Fire Propagation: tested acc to BS 476 Part 6:1989
	Surface Spread of Flame	Class 1				
	Fire propagation	Total index performance (I) ≤ 12 Sub index (i _s) ≤ 6				
Other Fire Class	FM-approved UL-94 HB, V - 0					Tested acc. to UL-94
Practical Fire Behavior	Self-extinguishing, does not drip and does not spread flames					
Chemical Behaviour	Excellent resistance to ozone, oil and chemicals (consult product test list)					
UV Resistance	Not recommended for outdoors					
Storage & Shelf life	Shall be stored in dry & clean area, away from direct sunlight					

All data and technical information are based on results achieved under typical application conditions. Recipients of this information should, in their own interest and responsibility, clarify with us in due time whether or not the data and information apply to the intended application area. Installation instructions are available in our Armaflex installation manual.

Armacell India Pvt. Ltd.

GAT No. 744-745, Village Lonikand, Pune Nagar Road • 412216 Pune •

Maharashtra • India

Phone +91 20 66782000

www.armacell.com • info.isa@armacell.com

CIN: U24293PN2005FTC131939