



MAXPLY[®] PRIMER

WATER-BASED BITUMINOUS EMULSION

DESCRIPTION

MAXPLY[®] PRIMER is a water-based bituminous emulsion specially designed to prime and prepare mortar, metallic sheets and wood before welding bituminous sheets in roofs.

It complies with the specifications required by UNE 104-231 (type B).

Solvent-free and non-flammable primer.

Apply by brush, roller or airless spray machine.
Consumption between 0,2 to 0,4 kg/ m² per coat, depending on substrate and porosity.

Available in packaging of 5 kg and 25 kg drums.
Shelf life 12 months kept under cover, protected from direct sunlight, humidity and freezing, with temperature between 5 °C and 40 °C.

GUARANTEE

The information contained in this leaflet is based on our experience and technical knowledge, obtained through laboratory testing and from bibliographic material. **DRIZORO[®], S.A.U.** reserves the right to introduce changes without prior notice. Any use of this data beyond the purposes expressly specified in the leaflet will not be the Company's responsibility unless authorised by us. We shall not accept responsibility exceeding the value of the purchased product. The data shown on consumptions, measurement and yields are for guidance only and based on our experience. These data are subject to variation due to the specific atmospheric and jobsite conditions so reasonable variations from the data may be experienced. In order to know the real data, a test on the jobsite must be done, and it will be carried out under the client responsibility. We shall not accept responsibility exceeding the value of the purchased product. For any other doubt, consult our Technical Department. This version of bulletin replaces the previous one.



DRIZORO, S.A.U.

C/ Primavera 50-52 Parque Industrial Las Monjas
28850 TORREJON DE ARDOZ – MADRID (SPAIN)
Tel. 91 676 66 76 - 91 677 61 75 Fax. 91 675 78 13
e-mail: info@drizoro.com Web site: drizoro.com

ISO 9001
ISO 14001

BUREAU VERITAS
Certification

n°ES021542 / ES021543

